



Enitra Sp. z o.o. ul. 1 Maja 62
58-300 Walbrzych
Tel. (0-74) 887-02-20 do 25
Fax (0-74) 843-91-40; 887-02-23
e-mail: enitra@enitra.pl
internet: www.enitra.pl

Elevator belts selection
survey
Zał. nr P.18-16

DATE

Necessary data for elevator belt selection		
1	B – belt width [mm]	
2	L – total belt length with additional space for splicing section [mb]	
3	Lifting hight [m]	
4	Performance [t/h]	
5	What kind of materia lis transportated?	
6	Humidity of products carried? [%]	
7	Belt speed (m/s) or drive pulley speed [1/min]	
8	Bulk density of material carried [t/m ³ lub kg/l]	
9	Drive pulley diameter [mm]	
10	Elevator bucket quantity [pcs/mb]	
11	Z1 – Bucket capacity specyified as Z ₁ [l] 	12 Bucket weight (empty) (kg)
13	Additional belt requirements: • Oil and fat resistance , FDA , Anti-static , ATEX • Workin temperature (°C).....Flame retardant • Abrasion resistance : W ≤, 90 mm ³ X ≤, 120 mm ³ Y ≤, 150 mm ³ Z ≤, 250 mm ³ • Other	
15	Fasteners required no yes	
16	Elevator buckets required no yes (Please fill out survey for elevاتور bucket selection)	

General Customer Details:

Name/Surname.....Phone/Fax.....
 Company Name.....
 Address.....
 Contact person.....